














EQUIPMENT	INTERIOR DIMENSIONS	DOOR OPENING	TOP OPENING	TARE WEIGHT	CUBIC CAPACITY	PAYLOAD*
45' High Cube Container 	L: 13.582 m W: 2.347 m H: 2.690	W: 2.340 m H: 2.584 m		4,110 kg	85.7 cbm	28,390 kg
40' High Cuber Container 	L: 12.056 m W: 2.347 m H: 2.684 m	W: 2.340 m H: 2.585 m		2,900 kg	76.0 cbm	29,600 kg
40' Dry Freight Container 	L: 12.051 m W: 2.340 m H: 2.380 m	W: 2.286 m H: 2.278 m		3,084 kg 3,630 kg(steel)	67.3 cbm	27,397 kg
20' Dry Freight Container 	L: 5.919 m W: 2.340 m H: 2.380 m	W: 2.286 m H: 2.278 m		1,900 kg	33.0 cbm	22,100 kg
20' Open Top Container 	L: 5.919 m W: 2.340 m H: 2.286 m	W: 2.286 m H: 2.251 m	L: 5.425 m W: 2.222 m	2,174 kg	31.6 cbm	21,826 kg
40' Open Container 	L: 12.043 m W: 2.338 m H: 2.272 m	W: 2.279 m H: 2.272 m	L: 11.585 m W: 2.162 m	4,300 kg	64.0 cbm	26,181 kg
45' High Cube Reefer Container 	L: 13.102 m W: 2.294 m H: 2.509 m	H: 2.467 m W: 2.290 m		5,200 kg	75.4 cbm	28,350 kg
40' High Cube Reefer Container 	L: 11.557 m W: 2.286 m H: 2.491 m	W: 2.286 m H: 2.454 m		4,320 kg	65.8 cbm	28,180 kg
40' Reefer Container 	L: 11.207 m W: 2.246 m H: 2.183 m	W: 2.216 m H: 2.183 m		4,600 kg	54.9 cbm	25,881 kg
20' Flat Rack Container 	L: 5.702 m W: 2.438 m H: 2.327 m			2,330 kg		21,670 kg
40' Flat Rack Container 	L: 11.820 m W: 2.148 m H: 2.095 m			5,260 kg		25,220 kg
40' Artificial Tweendeck 	L: 12.065 m W: 2.216 m			5,400 kg		39,000 kg
40' Collapsible Flat Rack 	L: 12.08 m W: 2.126 m H: 2.043 m			5,800 kg		29,200 kg

*Payload details are subject to prevailing over-the-road weight limitations applicable in individual countries and states. †Payload varies-----check container doors.